

US009636212B2

(12) United States Patent

Tiedtke et al.

(10) Patent No.: US 9,636,212 B2

(45) **Date of Patent:** May 2, 2017

(54) DEVICE FOR REVERSIBLY ATTACHING AN IMPLANT IN AN EYE

 $(75) \quad Inventors: \ \, \textbf{Hans-J\"{u}rgen} \,\, \textbf{Tiedtke}, \, Bonn \,\, (DE);$

Alexander Meyer, Bonn (DE)

(73) Assignee: PIXIUM VISION SA, Paris (FR)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 1516 days.

(21) Appl. No.: 12/293,788

(22) PCT Filed: Jan. 26, 2007

(86) PCT No.: PCT/EP2007/000684

§ 371 (c)(1),

(2), (4) Date: Nov. 10, 2010

(87) PCT Pub. No.: WO2007/118526

PCT Pub. Date: Oct. 25, 2007

(65) **Prior Publication Data**

US 2011/0071627 A1 Mar. 24, 2011

(30) Foreign Application Priority Data

Mar. 31, 2006 (DE) 10 2006 015 113

(51) Int. Cl.

 A61F 2/14
 (2006.01)

 A61F 9/007
 (2006.01)

 A61N 1/05
 (2006.01)

(52) U.S. Cl.

(58) Field of Classification Search

CPC A61F 2/14; A61F 2/147; A61F 9/0017; A61F 9/00781; A61F 9/007; A61F 9/00727; A61F 2220/00–2220/0033 (Continued)

(56) References Cited

U.S. PATENT DOCUMENTS

FOREIGN PATENT DOCUMENTS

EP 0 138 564 B1 4/1985 JP 4130589 B2 5/2008 (Continued)

OTHER PUBLICATIONS

PCT International Preliminary Report on Patentability relating to International Application No. PCT/EP2007/000684, date of issuance of this report Nov. 17, 2008 (1 pg.).

(Continued)

Primary Examiner — Paul Prebilic (74) Attorney, Agent, or Firm — Workman Nydegger

(57) ABSTRACT

The object of providing a device for reversibly attaching an implant to an eye, with which the implant can be attached in a simple way to the eye and can if necessary be detached or removed from the eye, is achieved according to the present invention by means of a device for attaching an implant by means of a pin that comprises a substantially elongated shaft, wherein the implant includes an implant film for contacting living tissue or nerves in the visual system of the eye and the implant film has an opening through which the shaft of the pin can be at least partially inserted, characterised in that the device includes a holding element that can be arranged on the shaft of the pin so that the holding element engages on the shaft of the pin and is fixed in an attachment position to the pin. By means of the device according to the invention the implant is on the one hand reliably attached, but can if necessary be detached from the retina by removing the holding element or retainer, wherein the pin anchored in the eye does not have to be removed at the same time, but can be re-used. Damage or injury to the tissue of the eye that (Continued)



